2023 CAN-AM MAVERICK X3 X RS TURBO RR

WITH SMART-SHOX



PACKAGE HIGHLIGHTS

- 200 hp. turbo charged Rotax powerplant with intercooler
- 72.7 in. wide with over 55cm of suspension travel
- · Smart-Lok front differential
- Smart-Shox Technology featuring DDA Valve
- FOX[†] 3.0 PODIUM[†] shocks with bypass
- Belt monitoring system
- 850 W magneto
- 7.6 in. digital display with keypad
- X-package graphics/seats
- · 4-point harness with shoulder pads
- Can-Am LED signature lights
- 14 in. aluminum beadlock wheels
- 32 in. Maxxis Carnivore† tyres
- Full roof
- HMWPE full skid plate

Intense Blue, Carbon Black, & Chalk Gray / TURBO RR

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4 modes traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/22 in. (55.9 cm) travel/ Trophy truck inspired arms
Front Shocks	FOX 2.5 PODIUM Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM remote reservoir with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
TYRES & WHEELS	
Front Tyres	Maxxis Carnivore [†] 32 x 10 x 14 in.
Rear Tyres	Maxxis Carnivore [†] 32 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,699 lb (770.7 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ® Quick-Attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)
Person Capacity	2

FEATURES

7.6 in. wide digital display with keypad
DC outlet (10-A)
RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
LED headlight, LED signature lights, LED tail lights
N/A
850 W
Integrated front bumper, quarter doors, full roof, 4-point harness with shoulder pads, HMWPE full skid plate, rear tow hook

WARRANTY & EXTENDED SERVICE

Factory Warranty	2 years / 15,000 km, whichever comes first
Service Intervals	100 hours / 12 months / 3000 km



